

O-Ring [Viton]

Applied Analytics DS-208A

Revised 13 May 2014



Applied Analytics flow cells and probes use o-rings to create safe seals and prevent any sample leaks. To properly handle hot, corrosive sample fluids, we use chemical-resistant, ultra-durable o-rings that are tested vigorously.

Technical Data	
Material of Construction	Viton
Temperature Range	-15 to 400 °F
Durometer Hardness	A75
Color	Black
Certifications/Compliance	ASTM D2000 SAE J200



is a registered trademark of Applied Analytics Group BV. | www.a-a-inc.com

Headquarters + Manufacturing

Applied Analytics, Inc.
Burlington, MA | sales@a-a-inc.com

North America Sales

Applied Analytics North America, Ltd.
Houston, TX | sales@appliedanalytics.us

Europe Sales

Applied Analytics Europe, AG
Geneva | sales@appliedanalytics.eu

Asia Pacific Sales

Applied Analytics Asia Pte. Ltd.
Singapore | sales@appliedanalytics.com.sg

Middle East Sales

Applied Analytics Middle East (FZE)
Sharjah, UAE | sales@appliedanalytics.ae

Brazil Sales

Applied Analytics do Brasil
Rio de Janeiro, Brazil | sales@aadbl.com.br

India Sales

Applied Analytics (India) Pte. Ltd.
Mumbai, India | sales@appliedanalytics.in

© 2013 Applied Analytics Group BV. Products or references stated may be trademarks or registered trademarks of their respective owners. All rights reserved. We reserve the right to make technical changes or modify this document without prior notice. Regarding purchase orders, agreed-upon details shall prevail.