

Collimator [All Options]

Applied Analytics Data Sheet No. DS-209X — Revised 11 April 2017



The collimators are inserted directly into either end of the flow cell. Fiber optic cables are inserted directly into the SMA 905 openings in the collimators. The function of the collimators is to create a parallel ray alignment in the signal, such that light dispersion is virtually eradicated.

The optical window material is specified by application and depends on the abrasive properties of the stream. This component represents the crossover between wetted/non-wetted parts, protecting the fiber optics from sample exposure.

- » Collimates light signal entering/exiting the flow cell
- » Unique one-piece design combines collimator, optical window, and sample seal into one solid component
- » Tightened using 9/16" wrench

Technical Data

Body Material	Stainless Steel
Window Material	Options: quartz (fused silica); sapphire; BaF
Maximum Temperature	300 °F
Connection	SMA 905



is a registered trademark of Applied Analytics, Inc. | www.aai.solutions

Headquarters

Applied Analytics, Inc.
Burlington, MA | sales@aai.solutions

Asia Pacific Sales

Applied Analytics Asia Pte. Ltd.
Singapore | sales@appliedanalytics.com.sg

India Sales

Applied Analytics (India) Pte. Ltd.
Mumbai, India | sales@appliedanalytics.in

North America Sales

Applied Analytics North America, Ltd.
Houston, TX | sales@appliedanalytics.us

Middle East Sales

Applied Analytics Oil & Gas Operations, L.L.C.
Abu Dhabi, UAE | sales@appliedanalytics.ae

Europe Sales

Applied Analytics Europe, AG
Genève, Switzerland | sales@appliedanalytics.eu

Brazil Sales

Applied Analytics do Brasil

Rio de Janeiro, Brazil | vendas@aadbl.com.br

© 2017 Applied Analytics, Inc. Products or references stated may be trademarks or registered trademarks of their respective owners. All rights reserved. We reserve the right to make technical changes or modify this document without prior notice. Regarding purchase orders, agreed-upon details shall prevail.